



BRICKFORM® Antique-It™

Antiquing Agent

PRODUCT DESCRIPTION

BRICKFORM Antique-It is a water soluble antiquing agent designed to impart a secondary color or highlight over stamped concrete or textured overlays. Antique-It is easy to apply, dries fast and provides a durable color that closely resembles the look of release powder.

LIMITATIONS

When applying to existing concrete, the surface must be properly profiled.

PACKAGING

BRICKFORM Antique-It comes in powder form and is packaged in a one gallon bucket.

COVERAGE

BRICKFORM Antique-It will cover 2000 to 3000 square feet per 3 lb container.

COLORS

BRICKFORM Antique-It is available in all 40 standard colors.

PREPARATION

When applying over freshly poured concrete or overlays, no preparation is needed other than to make sure the surface is clean and free of debris. Over existing concrete the surface must be profiled to the recommended ICRI CSP-1 profile outlined on Guideline No 03732; Selecting and Specifying Concrete Surface for Sealer, Coatings and polymer Overlays. The surface should be free from all sealers, dirt, oil, paint, moss, dust, and other contaminants. Proper and complete substrate surface preparation is critical to the success of the project.

APPLICATION

Pour one gallon of clean water into a 5-gallon pail, add 6 ounces of Antique-It powder to the water and mix vigorously until all powder has been dissolved. Add mix to a pump sprayer and apply evenly over the entire surface to be treated while continuously shaking the sprayer to keep particles suspended, avoid pooling the material in on spot, excessive spray may be removed with a sponge or wet rag. The ratio of water to Antique-It powder may be increased or decreased depending on the amount of color wanted.

SEALING

Allow Antique-It to dry for 2 to 4 hours before sealing. Apply at least two coats of Gem-Seal or Poly-Seal. Please consult the BRICKFORM TIS for any sealer used before using any of these sealers.

MAINTENANCE

The sealed surface should be inspected periodically for areas of thin or traffic worn sealer and re-applied as needed.

WARRANTY

This product is not intended for public use and is intended for use by trained, professional contractors and installers. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

BRICKFORM, A Division of Solomon Colors, Inc.
4050 Color Plant Rd
Springfield Il 62702

Toll Free 1-800-483-9628

www.brickform.com